

12

EUROPEAN PATENT APPLICATION

21 Application number: 83200733.0

51 Int. Cl.³: B 65 H 3/08

22 Date of filing: 25.05.83

30 Priority: 25.05.82 GB 8215349

43 Date of publication of application:
30.11.83 Bulletin 83/48

84 Designated Contracting States:
BE DE FR GB

71 Applicant: AGFA-GEVAERT naamloze vennootschap
Septestraat 27
B-2510 Mortsel(BE)

72 Inventor: Nelen, Petrus Renatus
Paviljoenweg 13
B-2190 Essen(BE)

64 An object holding device of sucker-cup type and sheet dispensing apparatus incorporating such device.

67 An object holding device is described wherein a cup component (8) comprising an elastically deformable sucker cup (18) and an associated air vent passage (9) is urged by spring means (15) into a position in which the end of such passage remote from the sucker cup is closed off by a sealing element (17) on a supporting body (10) in which the cup component is mounted. For releasing an object held by the cup the body (10) and cup component (8) have merely to be relatively displaced against the spring bias to unseal the vent passage (9).




FIG. 1

EP 0 095 218 A1

An object holding device of sucker-cup type and sheet dispensing apparatus incorporating such device

There are various known designs of object holding devices using sucker cups. The holding action of such cups depends upon the expulsion or exhaustion of air from within the cup while it is in contact with a surface of the object to be held.

Such holding devices are extensively used in sheet dispensers for the purpose of sequentially transferring sheets from one place to another, e.g. from a sheet stack holder to a position from or at which the sheets are handled or treated automatically by other means. Such dispensers are used for example in printing machines and document copying machines.

Prior art holding devices of sucker-cup type require to be coupled to a power source for controlling the suction effect. In some devices the sucker cup is connected to a vacuum source or an aspirator the action of which has to be controlled for causing an object to become held or released at an appropriate time. Another known device incorporates a flexible sucker cup which becomes deformed when pressed against an object to be held, with the result that air is expelled from within the cup, and incorporates a solenoid-controlled valve by which the interior of the cup can be placed in communication with atmosphere to cause release of the held object (see French Patent 2 105 164).

The necessity to provide a power source and associated switch or valve means is a disadvantage from the standpoints of convenience and cost. Particular problems are encountered when attempting to design a sheet dispensing apparatus incorporating a plurality of such holding devices suitably distributed for taking up sheets from a stack of sheets of different sizes. When a sheet to be picked up lies on a larger sheet, the cup or cups moving against the exposed part of the underlying sheet must be independently power controlled so that such underlying sheet is not taken up together with the top one.

It is an object of the present invention to provide an object holding device of sucker-cup type which does not require to be coupled to a power source for controlling the suction effect.

An object holding device according to the invention is defined in GV.1201

- 2 -

claim 1 hereof. The invention is characterised by the provision of a sucker cup component comprising the sucker cup and an air vent passage, such component being elastically biased, e.g. by a mechanical spring, towards a retracted position in relation to a body by which said component is supported, in which retracted position the end of said vent passage remote from the sucker cup is closed off by a sealing portion on the supporting body.

By this combination of features the need for an extraneous power source for controlling the suction effect is avoided. For taking hold of a sheet or other object the device has merely to be pressed against the object to cause deformation of and expulsion of air from within the cup. In order to release the object it is merely necessary to displace the cup component against the biasing force and thereby remove the vent passage from sealing relationship with the sealing portion on the supporting body. For effecting this displacement, force can be exerted directly on the sucker cup or on the object held thereby.

The sealing portion is preferably an elastically deformable element fitted into or onto a rigid part of the said body which supports the cup component.

In one embodiment of the invention, the vent passage is formed by a tube which is connected to the sucker cup and is axially slidable in said supporting body. This is a simple way of mounting the cup component and providing the required vent passage.

In another embodiment of the invention the cup component comprises a stem on which the sucker cup is mounted and which is axially slidable in the aforesaid supporting body, and also comprises a collar which surrounds said stem; and the end of the vent passage remote from the sucker cup is in a surface of such collar, which surface is pressed against said sealing portion by the biasing means. This combination of features also favours a simple construction, and enables the co-operating sealing faces to be easily accessible for cleaning.

The invention also includes a sheet dispensing apparatus incorporating a holding device according to the invention as above defined. Such an apparatus is defined in claim 6 hereof. That apparatus incorporates hold-releasing means which at the sheet
GV.1201

- 3 -

release stage of an operating cycle causes the cup component to advance relative to its supporting body, thereby placing the interior of the sucker cup in communication with atmosphere via the vent passage. The apparatus can incorporate a plurality of holding devices according to the invention, mounted for bodily movement in unison.

In a preferred embodiment the said hold-releasing means comprises an oscillating bar or bars located so as, at the appropriate stage of the dispensing cycle, to bear against a sheet held by the sucker cup. Actuation of the oscillating bar(s) may occur as a function of time in a dispensing cycle or in dependence on the spatial position acquired by the sheet in course of being dispensed.

A sheet dispensing apparatus according to the invention is very advantageous for use in dispensing metal, e.g. aluminium, printing plates or printing plate blanks of different sizes, for example printing plates produced by electrophotographic offset platemakers.

Certain embodiments of the invention, selected by way of example, will now be described with reference to the accompanying drawings, in which :

Fig. 1 shows one form of holding device according to the invention,

Fig. 2 shows another form of holding device according to the invention, and

Fig. 3 shows part of a sheet dispensing apparatus incorporating holding devices according to the invention.

The holding device shown in Fig. 1 comprises a supporting body 10 which includes cylindrical members 11 and 12 fixed one in the other. Member 11 is provided with a transverse rectangular section groove 13 for the purpose of mounting the device on a carrier bar (not shown) when the device is installed in a sheet dispensing apparatus. A cover member 14 is releasably secured to the member 11 e.g. by screws, so that it can be removed to permit the holding device to be easily removed from the bar.

The member 12 has a central bore of which an upper part 12a is of larger diameter than the other part of the bore. The upper part 12a accommodates a biasing means in the form of a helical spring 15.

A cup component, comprising an elastically deformable sucker cup
GV.1201

- 4 -

18 and a tube 16, is fitted to the supporting body 10 so that the cup component is axially displaceable relative to such body. The tube 16, to which the sucker cup 18 is secured, is slidable in the bore of the body member 12. The tube has an enlarged head portion which is accommodated in the wider upper part 12 of that bore and provides a bearing face for one end of the spring 15. The spring 15 exerts an upward force on the cup component 8 and thereby holds the upper end of tube 16 against a sealing element 17 of elastically deformable material which is fitted into a recess in the member 11. In this retracted position of the cup component 8 the said sealing element therefore seals off the upper end of the vent passage 9 extending along the tube 16 and through the underlying hub portion of the sucker cup 18.

In order to take hold of a sheet lying on a support, the illustrated device has merely to be pressed downwardly onto the sheet. This causes deformation of the sucker cup 18 and consequent expulsion of air from its interior, the air escaping between the cup and the sheet. When it is required to release the sheet it is merely necessary to cause relative axial recession of the body 10 and cup component 8 against the biasing force of spring 15. This can be done e.g. by raising the body 10 while restraining pressure is exerted on the sheet held by the cup, or by moving the cup 18 in a direction away from the body 10 while the latter is held stationary. Such movement can be effected by applying pressure against an object held by the cup, or directly against the cup itself or an attached part, e.g. a collar (if provided). The consequent separation of the sealing element 17 from the upper end of tube 16 places the vent passage 9 in communication with atmosphere in the widened bore 12a and the hold of the sucker cup on the sheet is therefore released.

In Fig. 2 the same reference numerals are used as in Fig. 1 to designate corresponding parts. The device shown in Fig. 2 differs from the Fig. 1 device in that the sucker cup 18 is mounted on a solid stem 19 in the lower end portion of which a portion of the vent passage 9a is formed. The stem is surrounded by a collar 17b in which an adjoining portion of such vent passage is formed. The upper extremity of the vent passage is located in the upper face of the collar 17b. The supporting body 10 is provided at its bottom end

GV.1201

with a sealing element 17a of elastically deformable material and the collar 17b is normally held pressed against this sealing element by the force exerted by the spring 15.

The sheet dispensing apparatus 20 represented in Fig. 3 comprises a plurality of holding devices according to the invention having their supporting bodies 10 mounted on a carrier bar 21. The bar 21 is connected to a mechanism (not shown) by which the bar can be moved to and fro as indicated by arrow 22, and up and down as indicated by arrow 23. Such movements are arranged to displace the holding devices through an operating cycle for the purpose of transferring sheets one by one from a pick-up station to a delivery point represented by an aligning bar 25, ready for being further handled or treated in a particular way. When a sheet such as 24 has been brought by the holding devices to the delivery point, the held sheet has to be released. For this purpose the apparatus includes an oscillating bar 26 to which an oscillating motion as indicated by the arrows 27 can be imparted by pivoting arms 28. When the bar 26 is at the lowest point of its trajectory it bears against the sheet 24 and while the oscillating bar 26 is in that position, the carrier bar 21 is raised. Because the cup components are restrained from upward movement by their hold on the sheet 24, the upward movement of the bar causes the supporting bodies 10 to rise relatively to the cup components and in consequence the interiors of the cups 18 are placed in communication with atmosphere via the vent passages.

CLAIMS :

1. An objecting holding device comprising a flexible sucker cup (18) which by pressure against an object to be held becomes deformed with consequent expulsion of air from within the cup, a vent passage via which air can be admitted to the interior of the cup (18) to cause release of its hold on an object, and closure means for closing communication between said vent passage and atmosphere until such release is required, characterised in that a cup component (18) comprising said sucker cup (18) and said vent passage (9,9a) is connected to a supporting body (10) in a manner allowing advance and retraction of said cup component relative to said body (10); there is biasing means (15) which urges said cup component (8) into its retracted position; and said body (10) has a sealing portion (17,17a) by which the end of said vent passage (9,9a) remote from sucker cup (18) is closed off when said cup component is in its retracted position.

2. A device according to claim 1, wherein said vent passage (9) is formed by a tube (16) which is connected to the sucker cup (18) and is axially slidable in said supporting body (10).

3. A device according to claim 1, wherein said cup component (8) comprises a step (19) on which said sucker cup (18) is mounted and which is axially slidable in said supporting body (10), and also comprises a collar (17b) which surrounds said stem, and wherein the end of said vent passage (9a), remote from the sucker cup (18) is in a surface of such collar (17b) and that surface is pressed against said sealing portion (17a) by said biasing means (15).

4. A device according to any preceding claim, wherein said sealing portion (17,17a) is constituted by an elastically deformable element fitted into or onto a rigid part of said supporting body (10).

5. A device according to any preceding claim, wherein said biasing means (15) is a spring.



6. Sheet dispensing apparatus comprising a sheet holding device of flexible sucker-cup type, and mechanism for bodily displacing such device repetitively through an operating cycle for taking hold of a sheet at a pick-up station, displacing such sheet from that station to another position at which the sheet is released, and subsequently taking hold of another sheet at said pick-up station, characterised
GV.1201

- 7 -

in that said sheet holding device is a device according to any preceding claim and in that said apparatus includes sheet releasing means (26,28) which operates at the sheet release stage of said cycle to cause advance movement of the cup component (18) relative to said supporting body (10) against the action of said biasing means (15) thereby to open said vent passage (9,9a) to atmosphere.

7. Sheet dispensing apparatus according to claim 6, wherein said releasing means (26,28) effects said relative advance movement of the cup component by pressing against a sheet (24) held by the sucker cup (18).

8. Sheet dispensing apparatus according to claim 7, wherein said releasing means (26,28) comprises an oscillating bar or bars for pressing against a said sheet (24) held by said sucker cup.





European Patent
Office

EUROPEAN SEARCH REPORT

0095218
Application number

EP 83 20 0733

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl. 7)
A	GB-A-2 018 726 (McCALL PATTERN CO.) * Page 5, lines 10-115; figures 1,2 *	1,2,4,6	B 65 H 3/08
A	DE-A-1 806 451 (CALLIGARO) * Page 5, lines 3-19; figures *	1	
A	GB-A-1 547 776 (HARTLEY & SONS) * Page 1, lines 15-37 *	7	
A	DE-A-2 915 718 (VEB POLYGRAPH)		
			TECHNICAL FIELDS SEARCHED (Int. Cl. 7)
			B 65 H B 66 C B 65 G F 16 B
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 30-08-1983	Examiner LONCKE J.W.
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

Object-holding device of sucker cup type and sheet dispensing apparatus incorporating such device

Patent Number: US4548396
Publication date: 1985-10-22
Inventor(s): NELEN PETRUS R (BE)
Applicant(s): AGFA GEVAERT NV (BE)
Requested Patent: EP0095218, B1
Application Number: US19830498158 19830525
Priority Number(s): GB19820015349 19820526
IPC Classification: B65G59/04; B65H3/08; B65H3/42
EC Classification: B65G49/06B, B65H3/08B6, B66C1/02, F16B47/00
Equivalents: DE3367195D, JP59036046

Abstract

An object-holding device is described wherein a cup component comprising an elastically deformable sucker cup and an associated air vent passage communicating with the cup interior is urged by spring means into a position in which the end of such passage remote from the sucker cup is closed off by a sealing element on a supporting body in which the cup component is mounted for limited axial movement. For releasing an object held by the cup after the latter is pressed against the object, the body and cup component have merely to be relatively displaced against the spring bias to unseal the vent passage.

Data supplied from the esp@cenet database - I2

DOCKET NO: A-3742
SERIAL NO: _____
APPLICANT: R-H Helmstädt
LERNER AND GREENBERG P.A.
P.O. BOX 2480
HOLLYWOOD, FLORIDA 33022
TEL. (954) 925-1100